

Models	75 EFI	90 EFI	115 EFI / 115 EFI CT
Kilowatts	55.2	66.2	85
Max.RPM at Full Throttle	4500 - 5500	5000 - 6000	5000 - 6000
Cylinders	4 (in-line)	4 (in-line)	4 (in-line)
Smart Craft Compatible	YES	YES	YES
Displacement	2064 cc	2064 cc	2064 cc
Starting	Electric	Electric	Electric
Gear Ratio	2.07:1	2.07:1	2.07:1 / 2.38:1
Gear Shift	F-N-R	F-N-R	F-N-R
Steering Midsection	Remote - BTO	Remote - BTO	Remote - BTO
Alternator System	35 amp (441 W)	35 amp (441 W)	35 amp (441 W)
Fuel System	EFI	EFI	EFI
Trim Positions	EHPT	EHPT	EHPT
Fuel Tank	N/A	N/A	N/A
Fuel Requirements	UL95R	UL95R	UL95R
Weight	163 kg	163 kg	163 kg / 165 kg
Available Boat Transom Heights	L - XL	L - XL	L - XL
Counter Rotation	N/A	N/A	N/A / CXL

GEAR SHIFT **DTS:** Digital Throttle and Shift • **F-N-R:** Mechanical Forward Neutral Reverse • **F-N:** Forward Neutral

STEERING MIDSECTION **AMS:** Advanced Mid Section • **CMS:** Conventional Mid Section
EHPS: Electric Hydraulic Power Steering
BTO: Big Tiller Optional • **RO:** Remote optional

ALTERNATOR SYSTEM **ESM:** On Electric Start Models only • **OPT:** Optional
OPT: Optional 4 amp (50 W) lighting, 2 amp (25 W) charging
ML: ML Models only

FUEL SYSTEM **EFI:** Electronic Fuel Injection • **Sci:** Super Charge Injection
DFI: Direct Fuel Injection • **CARB:** through carburetor

TRIM SYSTEM **EHPT:** Electric Hydraulic Power Trim and Tilt • **EHT:** Electric Hydraulic Tilt (no Trim) • **GAT:** Gas assist trim • **GMTT:** Manual Trim and Tilt
SWD: Shallow Water drive

FUEL TANK **INT:** Integrated fuel tank • **RO:** remote optional

AVAILABLE BOAT
TRANSOM HEIGHTS 381 mm(S) - 508 mm(L) - 635 mm(XL) - 762 mm(XXL)
COUNTER ROTATION 635 mm(CXL) - 762 mm(CXXL)

