Commercial calibration

Marathon engines are specifically calibrated to achieve a much longer engine life, ensuring reliability and performance when you need it most.

Fuel-efficient

Most FourStroke engines have up to 30% better fuel efficiency than TwoStrokes, allowing you to go further on less fuel.

Corrosion resistance

Mariner's proprietary formula, XK360, is an extremely low-copper-content aluminium alloy, which leads the industry in corrosion resistance. Costly corrosion failures and high labour bills are a thing of the past.

Lightweight

Lightweight, durable materials and fewer moving parts than competitive FourStroke engines have made the Marathon tough, compact, durable and highly efficient.

Model	30 MARATHON	50 MARATHON	60 MARATHON	90 MARATHON
Kilowatts (HP)	22.06 (30)	36.77 (50)	44.12 (60)	66.2 (90)
Max. RPM at full throttle	4000	5000		
Cylinders		4 (in-line)		
Displacement	1.0 litre	2.1 litre		3.0 litre
Starting		Electric		
Gear Ratio	2.33 : 1	2.38 : 1		1.92 : 1
Gear Shift		F-N-R		
Steering	Remote steering	Big Tiller (optional)		Big Tiller (optional)
				Dual cable mechanical
		Dual cable mechanical Hydraulic steering	Electro-hydraulic power steering (optional) (dual only)	
				Hydraulic steering
Alternator System	18 amp	35 a	amp	60 amp (756 watt)
Trim Positions		Power Trim & Power Tilt		
Weight	118 kg	165	ō kg	206 kg
Recommended Boat Transom Height		508 mm (L)		508 mm (L) 635 (XL)
Induction System	2-valve single overhead cam	8-valve single overhead cam		
Equipment Included	Racor water fuel separator, rigging hose, key switch, propeller, SC1000 SmartCraft gauge, remote control box			